CHECK OF FINGERPRINTS

Technical Field

The present invention relates to a method of pre-
venting false acceptance in a system for checking finger-
prints, which comprises a sensor. The invention also
relates to a system for fingerprint checking, and a
5 computer-readable storage medium.

Background Art

It is known to use fingerprint checking systems to
control access to a protected object, for example infor-
mation or premises.

A fingerprint checking system can be divided broadly
10 into three parts – a sensor, a memory and a processor.
The sensor is used to record fingerprints. The processor
compares the fingerprint recorded by the sensor with a
previously recorded reference fingerprint, what is known
as a template, which is stored in the memory. If the
15 recorded fingerprint corresponds to the reference finger-
print, the system accepts the recorded fingerprint and
allows access to the protected object.

Two terms used within this field are FAR (False
Acceptance Rate), in other words the frequency of false
20 acceptances, and FRR (False Rejection Rate), in other
words the frequency of false rejections. FAR is therefore
a measure of the probability that an unauthorised person,
whose fingerprint is not stored as a reference finger-
print in the system, will incorrectly gain access to the
25 protected object, and FRR is a measure of the probability
that an authorised person, whose fingerprint is stored as
a reference fingerprint in the system, will incorrectly
be denied access to the protected object. The ideal value
of both terms is 0.

30 When a fingerprint sensor is used, a finger is
placed against it. When the finger is removed from the
sensor, traces of the fingerprint may remain. There

traces may be caused by the usually greasy surface of the
finger, by other substances on the finger or by sub-
stances on the sensor. Such a residual fingerprint is
referred to below as a latent fingerprint. A latent

5   fingerprint constitutes a security problem because it can
be intensified and in the worst case lead to false
acceptance, in other words an unauthorised person gaining
access to the protected object.

        In many fingerprint checking systems, use is made of

10   silicon sensors, also called capacitive sensors. A sili-
con sensor utilises information about a fingerprint
having height differences and the finger having a spe-
cific resistance and a specific capacitance. In the event
that there is a latent fingerprint on a silicon sensor,

15   the sensor can be fooled into recording a fingerprint by
breathing lightly on it or cupping a hand over it. If
the latent fingerprint belongs to an authorised person,
an impostor can in this way fool the system into granting
him access to the protected object.

20   Optical sensors are another type of sensor used in
fingerprint checking systems. An optical sensor records
an image of the fingerprint if any part of the finger is
located sufficiently close to the sensor surface. In this
case, the law of total reflection applies. If there is

25   a latent fingerprint on the optical sensor, the system
can be fooled into recording and accepting a fingerprint
in spite of the fact that there is no finger on the
sensor by darkening the surface of the sensor. There is
therefore a risk that an unauthorised person will in this

30   way gain access to the protected object.

        The problem with latent fingerprints may occur in
any fingerprint sensor which requires the user's finger
to be in touch with the sensor surface and which records
the user's fingerprint by a single image. The problems

35   associated with latent fingerprints thus mean that FAR
has a high value.

3

Summary of the Invention

One object of the invention is therefore to solve the above-mentioned problems.

This object is partly or fully achieved by a method according to claim 1, a system according to claim 12 and
5   a storage medium according to claim 16.

According to a first aspect, the present invention thus relates to a method of preventing false acceptance in a system for checking fingerprints which comprises a sensor, comprising the step of detecting a latent finger-
10   print on the sensor.

Thus, according to the invention, the presence of a latent fingerprint on the sensor is detected, so that the latent fingerprint can be rejected. In this way, the risk is removed of an unauthorised person gaining access, by
15   means of a latent fingerprint, to the protected object, for example information or a room, which is protected by the system for fingerprint checking. One advantage of this method is that it is simple and can be used in existing systems. Furthermore, it does not require any
20   mechanical constructional changes. Nor does it require any complicated and time-consuming external treatment of the surface of the sensor in order to remove any latent fingerprints between recorded fingerprints.

As mentioned above, a latent fingerprint is a
25   fingerprint which remains on the sensor after the finger to which it belongs has been removed from the sensor.

It should be stressed that the method does not prevent false acceptances, which occur due to other reasons than latent fingerprints. Thus it reduces the
30   overall rate of false acceptance but prevents false acceptance due to latent fingerprints.

In one embodiment, the step of detecting a latent fingerprint comprises the steps of recording a finger-print by means of the sensor and, on the basis of the
35   location of the recorded fingerprint on the sensor, evaluating whether the recorded fingerprint originates

from a latent fingerprint on the sensor or from a finger placed on the sensor.

It would be possible to detect the latent fingerprint in various ways, for example by measuring the total
5   light level. However, using the location of the fingerprint on the sensor has proved to be a simple and neat solution. This is because the probability of two people one after the other placing their finger in exactly the same place on the sensor is very low, in the order of 1
10   in 1000. If, however, somebody attempts to use a latent fingerprint in order to fool the system, the latent fingerprint will be situated in exactly the same place as the "authentic" fingerprint. This distinction can be used in order to evaluate whether a recorded fingerprint ori-
15   ginates from a latent fingerprint or from an actual finger on the sensor.

In one embodiment, the evaluation step comprises, more specifically, comparing the location of the recorded fingerprint on the sensor with the location of a pre-
20   viously recorded fingerprint on the sensor.

This procedure is simple to implement, for example by means of a simple algorithm carried out in software or hardware. The location is easy to determine and the location of the previous fingerprint can be saved without
25   a heavy requirement for memory space.

One embodiment also comprises the step of, if the location of the recorded fingerprint on the sensor and the location of the previously recorded fingerprint essentially correspond, considering the recorded finger-
30   print as originating from a latent fingerprint. In this case, the fingerprint is rejected, access to the system thus being denied.

It is to be pointed out that the recorded fingerprint can in certain embodiments be considered as origi-
35   nating from a latent fingerprint if the difference in location lies within a predetermined narrow range, for example one or two pixels. Complete identity is therefore

not necessarily required, because the comparison algorithm can contain a degree of uncertainty.

It is usually sufficient to compare the recorded fingerprint with a single previously recorded finger-
5   print, because the latent fingerprint is destroyed when a new user places his finger against the sensor.

In one embodiment, the previously recorded fingerprint is the immediately preceding fingerprint which was considered as originating from a finger placed on the
10   sensor. This means that the previously recorded fingerprint may belong to an unauthorised person and that latent fingerprints of both authorised and unauthorised persons can be detected.

In an alternative embodiment, the previously record-
15   ed fingerprint is the immediately preceding fingerprint which was accepted, in other words considered as originating from an authorised person whose reference fingerprint is stored in the system.

Thus, according to the latter alternative only
20   fingerprints of authorised persons are stored as the previously recorded fingerprint. Thus, only latent fingerprints of authorised persons can be detected. If the latent fingerprint originates from an unauthorised person, the matching procedure can, however, take care
25   of the rejection of the latent fingerprint so that it does not result in a false acceptance. Alternatively, the check for latent fingerprint is carried out after the matching procedure, so that only fingerprints accepted by the matching procedure are tested.
30   One embodiment also comprises the step of storing the location of the recorded fingerprint on the sensor in the event that the recorded fingerprint is not considered as originating from a latent fingerprint.

The location of the recorded fingerprint may replace
35   a previously stored location of a previously recorded fingerprint. The fingerprint with which comparison is carried out for detection of a latent fingerprint may

therefore be changed continuously. Temporary storage of only one previously recorded fingerprint at a time is thus sufficientfor the purpose of detecting latent fingerprints.

5   In one embodiment, the location of a fingerprint on the sensor may be stored in a memory when the fingerprint is accepted as belonging to an authorised person. The location of this fingerprint may then be used for comparison with the location of later recorded finger-

10 prints until a new fingerprint is accepted. When the new fingerprint is accepted, the location of the previous fingerprint on the sensor is no longer required, and the location of the new accepted fingerprint can replace that of the previous one.

15   It is to be stressed that it is the location of the fingerprint in the coordinate system of the sensor which is stored. The entire previously recorded fingerprint can, but does not have to, be stored. In a memory-saving embodiment, the location of only certain partial areas or

20 certain points of the fingerprint is stored e.g. in the form of coordinates.

    In one embodiment, the step of comparing the loca-tion of the recorded fingerprint on the sensor with the location of a previously recorded fingerprint comprises

25 comparing the location on the sensor of at least one feature of the recorded fingerprint with the location of the corresponding feature of the previously recorded fingerprint.

    A common method used for fingerprint checking is

30 feature matching. In this method, a number of specific features are compared in order to decide whether a recorded fingerprint corresponds to a reference finger-print and thus originates from an authorised person.

    One or more such specific features can also be used

35 in order to detect a latent fingerprint. More specifi-cally, the locations of these features on the sensor are compared for the current recorded fingerprint and the

previously recorded fingerprint. If the features are
located in the same or essentially the same place on the
sensor in the two fingerprints compared, the current
recorded fingerprint is considered as originating from a
5   latent fingerprint. A feature may be, for example, the
end of a fingerprint line or a split of a fingerprint
line.

An alternative method used in fingerprint checking
is to match partial areas in a reference fingerprint
10   against a current recorded fingerprint in order to check
whether the partial areas are present in it and the
recorded fingerprint thus originates from an authorised
person. Partial areas can also be used for detection of
latent fingerprints, checking being effected on the basis
15   of the location of the partial areas on the sensor for
the current and the previously recorded fingerprint. This
alternative has the advantage that it is more reliable
than the method using specific features because, when the
location of partial areas on the sensor is compared, it
20   is known with greater certainty that corresponding areas
are actually being compared.

Thus, in one embodiment the step of comparing (130)
the location of the recorded fingerprint on the sensor
with the location of a previously recorded fingerprint
25   comprises comparing the location on the sensor of a
partial area of the recorded fingerprint with the loca-
tion of a corresponding partial area of the previously
recorded fingerprint.

As a further alternative, the location of the entire
30   fingerprint can be compared, e.g. by separating the
foreground and the background of the fingerprints so that
the locations of the contours of the fingerprints may be
compared or by matching the whole fingerprints.

A further embodiment may comprise the step of
35   matching (110) at least one partial area of a reference
fingerprint with the recorded fingerprint to obtain at
least one matching partial area of the recorded finger-

print, wherein the step of comparing the location of the
recorded fingerprint on the sensor with the location of a
previously recorded fingerprint comprises comparing the
location on the sensor of the matching partial area with
5. the location of the corresponding partial area of the
previously recorded fingerprint.

The reference fingerprint is a previously stored
fingerprint which belongs to an authorised person. The
reference fingerprint does not have to be a complete
10 fingerprint but can be a processed form thereof, what
is known as a template. The template can comprise e.g.
partial areas of the reference fingerprint or specific
features and their location.

It is to be pointed out that a plurality of refe-
15 rence fingerprints are usually stored, because there is
often more than one authorised person for the protected
object which the fingerprint checking system protects.
However, it is also possible for only one reference
fingerprint to be stored.

20 In one embodiment, the comparison of the location of
the recorded fingerprint on the sensor with the location
of a previously recorded fingerprint is carried out only
in the event that a matching between a reference finger-
print and the recorded fingerprint reveals that the
25 recorded fingerprint originates from an authorised
person.

According to this method, matching of the recorded
fingerprint is carried out first. Only if a reference
fingerprint is found, which corresponds to the recorded
30 fingerprint, is the location of the recorded fingerprint
on the sensor checked against the location of a previous-
ly recorded fingerprint on the sensor so as in this way
to decide whether the fingerprint is a latent fingerprint
or not. Location checking is thus not carried out if the
35 fingerprint is rejected on account of it not being con-
sidered as originating from an authorised person.

According to a second aspect, the invention relates to a system for fingerprint checking comprising a sensor, the system being arranged to detect a latent fingerprint on the sensor so as to prevent false acceptance.

According to a third aspect, the invention relates to a storage medium for digital information, which is readable for a computer system, the storage medium containing a computer program for preventing false acceptance in a system for checking fingerprints, said program defining the method in any one of claims 1-11.

What has been said above about the method also applies, where appropriate, to the system and the storage medium.

Brief Description of the Drawings

The invention will be described in greater detail below with reference to the accompanying drawings, in which

Fig. 1 shows schematically an embodiment of a system for fingerprint checking;

Fig. 2 is a flow diagram of an embodiment of the method according to the invention;

Fig. 3a shows an actual fingerprint, and

Fig. 3b shows a latent fingerprint.

Description of a Preferred Embodiment

Fig. 1 shows schematically a system for fingerprint checking. The system comprises essentially a sensor 1, comparison means 2 and a memory 3. The sensor 1 is arranged to record a fingerprint from a finger which is placed on the sensor, and to feed this to the comparison means 2. The sensor 1 can be of, for example, the capacitive or optical type. It has an integral coordinate system.

The comparison means 2 can take the form of hardware or software and, for example, include a microprocessor with suitable programs or a specifically adapted hardware, e.g. an ASIC (Application Specific Integrated Circuit) or an FPGA (Field Programmable Gate Array). The

output signal from the comparison means indicates in some manner whether the fingerprint recorded by the sensor is accepted, in other words that it originates from an authorised person whose reference fingerprint is stored

5   in the memory, or is rejected, in other words that it originates from an unauthorised person or is evaluated as originating from a latent fingerprint or cannot be accepted for another reason. The output signal can be used internally in the system, e.g. as a basis for

10 creating a lock-up signal or an access signal for a protected object, or be sent to an external unit, e.g. a display.

Stored in the memory 3 is/are one or more reference fingerprint(s) which is/are recorded under secure circum-

15 stances from one or more authorised people who is/are entitled to have access to the protected object which is protected by the system. The memory may be permanently connected to the comparison means 2 or temporarily connected. In the latter case it may consist of a smart

20 card or similar portable data carrier.

The recording of a reference fingerprint may be carried out as follows. The sensor captures a greyscale digital image of a fingerprint. A quality check is carried out to ensure that the sensor is capable of

25 distinguishing between "ridges" and "valleys" on the finger. Then the image is binarised. Binarisation means that the pixels of the image are compared with a grey-scale threshold value. Those pixels which have a value smaller than the greyscale threshold value are converted

30 to white and those which have a value greater than the greyscale threshold value are converted to black.

After binarisation, a number of partial areas of the image are selected for storage as a processed form of the reference fingerprint, also called a template. One of the

35 partial areas is selected so as to lie fairly centrally in the fingerprint. The others, the number of which usually varies between four and eight depending on the

level of security required, can have varying positions
in relation to the central area. The size of the partial
areas selected can be 48 x 48 pixels but can easily be
adapted by the person skilled in the art according to
5   existing requirements. The various partial areas can be
found by searching the image for areas with as much
individual-specific information as possible. Areas with
curved lines, for example, are of greater interest than
areas with straight parallel lines. The template, which
10   also comprises the relative locations of the other
partial areas in relation to the central area, is then
stored in the memory 3.

      The flow chart of Fig. 2 shows how fingerprint
checking is carried out when a user wishes to have access
15   to the protected object, for example sensitive informa-
tion or a locked passage, to which the system can grant
access by fingerprint checking. The user places his
finger on the sensor 1, and a digital sample image of the
fingerprint is recorded in a recording step 100 in the
20   same manner as above when the template was recorded,
apart from the fact that no areas are initially selected.
After recording, the sample fingerprint therefore has a
format which makes possible comparison with the template
which is stored in the memory 3.

25   The comparison means 2 are arranged to receive the
recorded sample fingerprint and match it in a matching
step 110 with the reference fingerprint(s) stored in the
memory 3. During matching, it is in this case checked
whether the partial areas of the template are present in
30   the recorded fingerprint. More particularly, the central
partial area of the template is matched against a central
part of the recorded sample fingerprint. If a match is
obtained, the relative location information of the
template is used to select partial areas of the sample
35   fingerprint. The partial areas of the sample fingerprint
are selected to have the same relative locations with
regard to the matching partial area of the sample finger-

print as have the other partial areas of the template with regard to the central partial area of the template. Finally, the partial areas of the template are matched against the selected partial areas of the sample finger-

5   print to determine whether a matching requirement is fulfilled. If so, the recorded sample fingerprint is considered as originating from an authorised person.

PCT/SE99/00553 describes a slightly different method for selecting the part areas of the sample fingerprint.

10   If the recorded fingerprint is not considered as originating from an authorised person, step 120, the fingerprint is rejected, step 125. If, however, it is considered as originating from an authorised person, the method continues with a check of whether the fingerprint

15   may be a latent fingerprint.

More specifically, the location on the sensor 1 of the recorded sample fingerprint is compared, in step 130, with the location on the sensor 1 of the immediately preceding accepted fingerprint. In this connection, use

20   is made of those partial areas of the recorded sample fingerprint which in step 110 were considered as matching the partial areas in the reference fingerprint. The locations of these matching partial areas in the coordinate system of the sensor are determined, for example the

25   central points of the partial areas can be used, and are compared with the locations of corresponding partial areas of the previously recorded fingerprint. If the location of at least one partial area is the same, step 140, the recorded fingerprint is considered as being

30   located in the same place as the previously recorded fingerprint. The result is that the recorded fingerprint is rejected, step 145, on account of the fact that it is considered to be a latent fingerprint. It should be stressed that also partial areas, the locations of which

35   deviate with one or a few pixels, may be considered as being located in the same place.

If none of the partial areas is located in the same place, the recorded fingerprint is considered as originating from an actual finger on the sensor. The locations on the sensor of the matching partial areas in the re-
5   corded fingerprint are then stored in the memory 3, step 150, as the location of a previously recorded fingerprint. More specifically, the coordinates of each of the partial areas are stored. The coordinates may be the coordinates of one or more predetermined points in the
10   partial areas, e.g. the central points or the corner points. The storage is only temporary and lasts only until a later recorded fingerprint is processed in step 150.

Finally, the recorded fingerprint is accepted in
15   step 155 as a fingerprint of an authorised person, and the system signals this appropriately, for example by means of a simple OK signal or a control signal which allows access to a protected object, for example a room or a computer.

20   Fig. 3a schematically shows a first image of an actual fingerprint recorded from a finger on a sensor. In the fingerprint, the location of the central points 4 of five partial areas are marked. Fig. 3b shows a second image of a recorded fingerprint which originates from a
25   latent fingerprint, which remained on the sensor after recording of the fingerprint in Fig. 3a. In Fig. 3b, the same partial areas have been found and the central points thereof are marked. Alternatively, the points 4 could illustrate the location on the sensor of correspon-
30   ding features. The fingerprint images are shown in a respective coordinate system, where R is the row coordinate axis and C is the column coordinate axis, to schematically indicate that the locations of the points 4 are the same. It is sufficient for the location of one point
35   (for example the coordinates of the central point of one partial area or the coordinates of one feature) to corre-

spond in the two fingerprints compared in order to con-
sider the location of the fingerprints as corresponding.

The comparison can be carried out by comparing the
coordinates of the points, and, if they are the same or
5   essentially the same, the current fingerprint is conside-
red as being a latent fingerprint which originates from
the preceding fingerprint, and the fingerprint is rejec-
ted. It has been found that a good limit value is if the
test points are separated by fewer than two pixels in the
10   x direction and the y direction. The limit value is then
compared with all the test points.

The comparison can be carried out as follows (semi
program code):

    For I = 1 to number of points

15   Do

```
            If abs(R1I-R2I)<2 and abs(C1I-C2I)<2
            Then
                    Latent Fingerprint present
                    Exit
20              End
        End
        Exit
```

Where R1I is the row coordinate of point I of the first
image, R2I is the row coordinate of point I of the second
25   image, C1I is the column coordinate of point I of the
first image, and C1I is the column coordinate of point I
of the second image.

If there are no time constraints, the entire image
or the entire detailed pattern can be compared.

30   <u>Alternative embodiments</u>

Although a special embodiment of the invention has
been described above, it is evident for the person
skilled in the art that many alternatives, modifications
and variations are possible in the light of the above
35   description.

Fig. 1 shows the sensor 1, the comparison means 2
and the memory 3 as separate physical units which are

interconnected by means of lines. Other variants are also possible. The sensor 1 and the comparison means 2 can, for example, be integrated with one another and located in the same physical unit which is connected to the

5 memory 3 which is located in another physical unit. The sensor 1, the comparison means 2 and the memory 3 can also all be integrated in a single physical unit.

In a further alternative, the memory 3 consists of a data carrier in the form of a personal card, e.g. a smart

10 card, on which the fingerprint of the owner is stored in electronic form so that it can be read into the comparison means 2 via a reader which can be located in the same physical unit as the sensor and the comparison unit.

It is also possible for the system to have a plura-

15 lity of sensors 1 which are connected to a central unit which contains the memory 3 for storing reference finger-prints and the comparison means 2. The system can contain a special reference sensor for recording reference fingerprints.

20 The fingerprint can be stored in the form of a bit map. An efficient algorithm for matching bit maps is described in Applicant's Swedish Patent Application SE 9704925-8.

Above, the matching of fingerprints has been descri-

25 bed as based on the comparison of partial areas of a current fingerprint with partial areas of a template. Alternatively, it may, however, be based on the comparison of specific features, also called minutiae points, of the current fingerprint and the template.

30 Furthermore, the detection of a latent fingerprint has been described as based on the comparison of the locations on the sensor of partial areas in a current fingerprint with the locations on the sensor of partial areas in a previously recorded fingerprint. The detection

35 can however also be carried out on the basis of the locations of corresponding features.

Another alternative is to extract the contour of the
current fingerprint and to compare its location on the
sensor with the location o the sensor of a contour of a
previously recorded fingerprint.

5   Yet another alternative is to match the entire
current fingerprint to the entire previously recorded
fingerprint and to determine whether they are located in
the same position on the sensor.

In the above-described embodiment, the location of
10   the previously recorded fingerprint is stored in the
memory 3, which may be a memory permanently or temporari-
ly connected to the comparison means 2. However, the
location of the previously recorded fingerprint may also
be stored in a memory in the sensor or in the same hard-
15   ware component as the sensor. The advantage with this is
that the system cannot be fooled by a switch of sensors.
Alternatively, the location of the previously recorded
fingerprint can be stored in conjunction with the temp-
late used for matching of the previously recorded finger-
20   print. Next time this particular template is used for
matching, the location of the sample fingerprint is
checked against the location of the previously recorded
fingerprint stored in conjunction with the template to
evaluate whether the sample fingerprint is a latent
25   fingerprint.